

DOCKET NUMBER: 95176562-024001
PATENT

IN THE CLAIMS:

This listing of the claims will replace all prior versions, and listings, of claims in the application:

1-32. (cancelled)

33. (currently amended) The substrate cutting device of claim 94, wherein said [A] cutter for producing substrate fibers comprising: comprises:

a leading edge, said leading edge initially contacting a substrate during a cutting stroke,
and

a trailing edge, ~~said leading edge initially contacting a substrate during a cutting stroke,~~
said trailing edge being raised a prescribed height above said leading edge;

a blade section disposed on a cutting surface of said cutter for cutting the substrate; and

at least one substrate fiber channel located proximate said blade,

wherein said substrate remains fixed and said cutter moves relative to said substrate during the cutting stroke along the predetermined cutting path to produce a plurality of substrate fibers, and wherein said plurality of substrate fibers are directed away from said substrate by said substrate fiber channel.

34. (currently amended) The substrate cutting device ~~cutter~~ of claim 33, wherein said blade section is elevated to a height defining a cutting thickness for said substrate fibers.

35. (currently amended) The substrate cutting device ~~cutter~~ of claim 33, wherein said prescribed height is equal to the elevated height of said blade section.

36. (currently amended) The substrate cutting device ~~cutter~~ of claim 33, wherein said blade section includes at least one row of teeth.

37. (currently amended) The substrate cutting device ~~cutter~~ of claim 36, wherein each tooth includes at least one predetermined cutting angle.

DOCKET NUMBER: 95176562-024001
PATENT

38. (currently amended) The substrate cutting device ~~utter~~ of claim 37, wherein each tooth includes a primary cutting angle and a secondary cutting angle.

39. (currently amended) The substrate cutting device ~~utter~~ of claim 38, wherein said primary cutting angle is between 3°-6°.

40. (currently amended) The substrate cutting device ~~utter~~ of claim 38, wherein said primary cutting angle is approximately 4°.

41. (currently amended) The substrate cutting device ~~utter~~ of claim 38, wherein said secondary cutting angle is between 10°-18°.

42. (currently amended) The substrate cutting device ~~utter~~ of claim 38, wherein said secondary cutting angle is between 12°-16°.

43. (currently amended) The substrate cutting device ~~utter~~ of claim 38, wherein said secondary cutting angle is approximately 14°.

44. (currently amended) The substrate cutting device ~~utter~~ of claim 36, wherein said substrate fiber channel is located proximate said at least one row of teeth.

45. (currently amended) The substrate cutting device ~~utter~~ of claim 33, wherein said substrate fiber channel has predetermined dimensions to promote cutting of substrate fibers having desired features.

46. (currently amended) The substrate cutting device ~~utter~~ of claim 33, wherein the substrate is bone.

47. (previously presented) A substrate cutting device comprising:

DOCKET NUMBER: 95176562-024001
PATENT

a base having a cutter mounted thereon, and a substrate chute extending through said base to position a substrate in contact with said cutter; and

a tower coupled to said base, wherein said tower comprises (a) a lower surface containing a recess therethrough, said recess being in alignment with said substrate chute, and (b) a clamping mechanism for keeping the substrate in contact with said cutter,

wherein said substrate remains fixed and said cutter moves relative to said substrate during a cutting stroke.

48. (original) The substrate cutting device of claim 47, further comprising a substrate fiber receptacle positioned beneath said cutter to receive substrate fibers cut from the substrate.

49. (original) The substrate cutting device of claim 47, further comprising a plurality of grooves formed along a contact surface of said clamping mechanism for reducing movement of the substrate while in contact with said cutter.

50. (original) The substrate cutting device of claim 47, further comprising a computer controller for controlling operation thereof.

51. (original) The substrate cutting device of claim 47, further comprising a sensor arrangement for detecting prescribed conditions during operation of said substrate cutting device.

52. (original) The substrate cutting device of claim 47, wherein said base further comprises a slide mechanism for receiving said cutter, and wherein said slide mechanism moves said cutter along said predetermined cutting path.

53. (original) The substrate cutting device of claim 52, wherein said cutter is rotated a predetermined amount relative to the cutting path to engage the substrate.

54. (original) The substrate cutting device of claim 52, further comprising a first actuation unit for moving said slide mechanism.

DOCKET NUMBER: 95176562-024001
PATENT

55. (original) The substrate cutting device of claim 54, further comprising a computer controller for controlling operation of said first actuation unit.

56. (original) The substrate cutting device of claim 55, wherein said computer controller variably controls the speed of said slide mechanism and a force applied to cut the substrate.

57. (original) The substrate cutting device of claim 54, wherein said first actuation unit applies a force of 600 lbs-900 lbs during said predetermined cutting stroke.

58. (original) The substrate cutting device of claim 54, wherein said first actuation unit applies a force of 700 lbs-800 lbs during said predetermined cutting stroke.

59. (original) The substrate cutting device of claim 54, wherein said first actuation unit applies a force of 750 lbs during said predetermined cutting stroke.

60. (original) The substrate cutting device of claim 54, wherein said first actuation unit is pneumatically operated at a predetermined constant pressure.

61. (original) The substrate cutting device of claim 54, wherein said first actuation unit is pneumatically operated at predetermined variable pressures.

62. (original) The substrate cutting device of claim 54, wherein said first actuation unit is hydraulically operated.

63. (original) The substrate cutting device of claim 54, wherein said first actuation unit is electrically operated.

64. (previously presented) The substrate cutting device of claim 47, wherein said cutter comprises a leading edge and a trailing edge, said leading edge initially contacting the substrate

DOCKET NUMBER: 95176562-024001
PATENT

during a cutting stroke, said trailing edge being raised a prescribed height above said leading edge; a blade section disposed on a cutting surface of said cutter for cutting the substrate; and at least one substrate fiber channel located proximate said blade section for directing substrate fibers away from the substrate.

65. (original) The substrate cutting device of claim 64, wherein said blade section is elevated to a cutting height defining a thickness for said substrate fibers.

66. (previously presented) The substrate cutting device of claim 65, wherein said thickness is equal to the cutting height of said blade section.

67. (original) The substrate cutting device of claim 64, wherein said blade section includes at least one row of teeth.

68. (original) The substrate cutting device of claim 67, wherein each tooth includes at least one predetermined cutting angle.

69. (original) The substrate cutting device of claim 67, wherein each tooth includes a primary cutting angle and a secondary cutting angle.

70. (original) The substrate cutting device of claim 69, wherein said primary cutting angle is between 3°-6°.

71. (original) The substrate cutting device of claim 69, wherein said primary cutting angle is approximately 4°.

72. (original) The substrate cutting device of claim 69, wherein said secondary cutting angle is between 10°-18°.

73. (original) The substrate cutting device of claim 69, wherein said secondary cutting angle is

DOCKET NUMBER: 95176562-024001
PATENT

between 12°-16°.

74. (original) The substrate cutting device of claim 69, wherein said secondary cutting angle is approximately 14°.

75. (previously presented) The substrate cutting device of claim 67, wherein said substrate fiber channel is located proximate said at least one row of teeth.

76. (original) The substrate cutting device of claim 64, wherein the trailing edge of said cutter is substantially flush with an upper surface of said slide mechanism.

77. (original) The substrate cutting device of claim 64, wherein said blade section engages the substrate such that the substrate fibers are cut substantially along a grain direction of the substrate.

78. (original) The substrate cutting device of claim 47, wherein said tower further comprises a second actuation unit for operating said clamping mechanism.

79. (original) The substrate cutting device of claim 78, wherein said second actuation unit applies a force of 150 lbs-250 lbs onto the substrate.

80. (original) The substrate cutting device of claim 78, wherein said second actuation unit applies a force of 200 lbs onto the substrate.

81. (original) The substrate cutting device of claim 78, wherein said second actuation unit is pneumatically operated at a predetermined constant pressure.

82. (original) The substrate cutting device of claim 78, wherein said second actuation unit is pneumatically operated at predetermined variable pressures.

DOCKET NUMBER: 95176562-024001
PATENT

83. (original) The substrate cutting device of claim 78, wherein said second actuation unit is hydraulically operated.

84. (original) The substrate cutting device of claim 78, wherein said second actuation unit is electrically operated.

85. (original) The substrate cutting device of claim 78, further comprising a computer controller for controlling operation of said second actuation unit.

86. (original) The substrate cutting device of claim 85, wherein said computer controller variably controls a force applied by said clamping mechanism.

87-93. (cancelled)

94. (previously presented) A substrate cutting device comprising:

a base;

a cutter mounted on said base, said cutter being movable along a predetermined cutting path;

a substrate chute extending through said base to position the substrate in contact with said cutter;

a tower coupled to said base having a lower surface containing a recess therethrough, said recess being in alignment with said substrate chute;

a clamping mechanism for keeping the substrate in contact with said cutter; and

a computer controller for controlling operation of said device.

95. (previously presented) A substrate cutting device comprising:

a base;

a cutter mounted on said base, said cutter being movable along a predetermined cutting path;

a substrate chute extending through said base to position the substrate in contact with said

DOCKET NUMBER: 95176562-024001
PATENT

cutter;

a tower coupled to said base having a lower surface containing a recess therethrough, said recess being in alignment with said substrate chute;

a clamping mechanism for keeping the substrate in contact with said cutter; and

a sensor arrangement for detecting prescribed conditions during operation of said substrate cutting device.

96. (previously presented) A substrate cutting device comprising:

a base;

a cutter mounted on said base, said cutter being movable along a predetermined cutting path, wherein said base comprises a slide mechanism for receiving said cutter, and wherein said slide mechanism moves said cutter along said predetermined cutting path;

a substrate chute extending through said base to position the substrate in contact with said cutter;

a tower coupled to said base having a lower surface containing a recess therethrough, said recess being in alignment with said substrate chute; and

a clamping mechanism for keeping the substrate in contact with said cutter.

97. (previously presented) A substrate cutting device comprising:

a base;

a cutter mounted on said base, said cutter being movable along a predetermined cutting path;

a substrate chute extending through said base to position the substrate in contact with said cutter;

a tower coupled to said base having a lower surface containing a recess therethrough, said recess being in alignment with said substrate chute; and

a clamping mechanism for keeping the substrate in contact with said cutter, wherein said tower further comprises a second actuation unit for operating said clamping mechanism.

98. (previously presented) A bone fiber cutting device for producing bone fiber that has a

DOCKET NUMBER: 95176562-024001
PATENT

textured surface, a lengthwise grain, and a plurality of parallel striations along the grain, comprising,

a cutter comprising a blade section;

a clamping mechanism for holding a bone tissue having a lengthwise grain;

a slide mechanism that is coupled to the cutter;

wherein the clamping mechanism is disposed relative to the slide mechanism so that the slide mechanism slides substantially parallel to the lengthwise grain of the clamped bone tissue and the blade section contacts the bone tissue during operation of the cutting device;

a first actuation unit that moves the slide mechanism during operation of the cutting device;

a second actuation unit that positions the clamping mechanism;

at least one fiber channel; and

a controller, wherein the controller controls the first actuation unit and the second actuation unit.

99. (previously presented) The bone fiber cutting device of claim 98, wherein the blade section includes at least one row of teeth.

100. (previously presented) The bone fiber cutting device of claim 98, further comprising a sensor for detecting prescribed conditions during operation of the cutting device.

101. (previously presented) The bone fiber cutting device of claim 98, wherein the controller varies a speed at which the slide mechanism slides during operation of the cutting device.

102. (previously presented) The bone filler cutting device of claim 98, wherein the controller varies a force at which the blade section contacts the bone tissue during operation of the cutting device.

103. (previously presented) The bone fiber cutting device of claim 98, wherein the first actuation unit is pneumatic.

DOCKET NUMBER: 95176562-024001
PATENT

104. (previously presented) The bone fiber cutting device of claim 98, wherein the first actuation unit is hydraulic.
105. (previously presented) The bone fiber cutting device of claim 98, wherein the first actuation unit is electric.
106. (previously presented) The bone fiber cutting device of claim 98, wherein the second actuation unit applies a force of 150 lbs-250 lbs to the clamping mechanism during operation of the cutting device.
107. (previously presented) The bone fiber cutting device of claim 98, wherein the second actuation unit applies a force of 200 lbs to the clamping mechanism during operation of the cutting device.
108. (previously presented) The bone fiber cutting device of claim 98, wherein the second actuation unit is pneumatic.
109. (previously presented) The bone fiber cutting device of claim 98, wherein the second actuation unit is hydraulic.
110. (previously presented) The bone fiber cutting device of claim 98, wherein the second actuation unit is electric.
111. (new) The substrate cutting device according to claims 47, 94, 95, 96, or 97, wherein the substrate is bone.